



Remark:
To save cost, our system use the separate power supply for indoor monitor, not the POE. Each 4/6 pcs indoor monitor use 1 pc power supply.

Advantages

- Use TCP/IP protocol base on LAN network, no distance and apartment quantity limitation, multi channel intercom.
- Use the digital compression technology to ensure quality sound and image.
- Powerful Functions: Integrate the functions of building intercom, message announcement, automatic home control system, image record, 8 security alarm zone, multimedia, photo album and so on.
- Easy installation, use international standard RJ45 socket, network switch.
- Easy Maintenance: Automatic fault detection, greatly reduce the labor cost.
- Support Remote upgrade, keep your system always be the latest.
- Friendly interface, easy use.



Air-condition controlling



Curtain controlling



TV/Stereo controlling



Light controlling



Elevator calling



Telephone unlock function

Features

- 7" TFT LCD display (9" or 10" TFT LCD is optional)
- Touch screen
- Melody ring tone to identify where the call come from.
- Intercom with outdoor station, management center
- Intercom between each apartment by input the room No/address.
- Monitor the outdoor station and other IP cameras.
- 8 alarm stations (Emergency button, Smoke, Gas, IR, Magnetic contact for door or curtain)
- Message receiving from management center.
- Image memory from outdoor station.
- Multimedia playing, Mp3, MP4 and photo album with SD card.
- Intelligent Home controlling, Light, Curtain, Air-condition etc, can set the scene (At Home, Out home, sleep, party etc.)
- Calendar, Time and date, Clock.
- Remote control unlocking, password unlocking.

TCP/IP time is coming!





Model: HIS-350

7" TFT LCD
Dimension: 248*147*26 (mm)
Installation: Surface mount



Model: HIS-410

10.2" TFT LCD
Dimension: 280*214*28.5 (mm)
Installation: Surface mount



Model: HIS-310

7" TFT LCD
Dimension: 239*139*31.2 (mm)
Installation: Surface mount



Model: HIS-330

7" TFT LCD
Dimension: 246*158*32.2 (mm)
Installation: Surface mount

Features

- Suitable for villa system and apartment system.
- Support extra 2pcs security cameras (Villa system only).
- The base can bi-intercom, monitoring and remote control unlock with outdoor station.
- Image record with building in SD card max. 100pcs pictures.(Optional)
- The connection between the handset and base is wireless with 1.8Ghz.
- The handset can support all DECT phone features, such as make or answer normal phone calls.
- The handset can have intercom with outdoor station and also support remote control unlock.
- Two installation type: Table type or surface mount.



Features: (For TCP/IP Apartment System)

- High-end metal surface.
- Touch panel.
- Intercom with every indoor monitor and outdoor station with record.
- Monitor and Remote unlock for every outdoor station.

Management Center

Model: A
9" TFT LCD
Dimension: 303*195*29.5 (mm)
Installation: Table type



Model: HIS-930

Color/B/W CCD
Dimension: 375*155*46.5(mm)
Build-in size: 359*139*51(mm)



Features:

- Touch Keypad
- Search Name and Room No(Optional)
- LED/LCD Display
- Intercom with indoor monitor
- Intercom with management center
- Support IC/ID card(Optional)
- Unlock by password
- Support 99, 999 indoor monitor
- Low temperature to -40°C (Optional)
- High quality image in night vision



Model: HIS-110

Color/B/W CCD
Dimension: 92*127*32 (mm)
Installation:Surface mount



Model: HIS-130

Color/B/W CCD
Dimension: 192*116*47 (mm)
Build-in size: 177.5*100.5*46.5(mm)



Model: HIS-140

Color/B/W CCD
Dimension: 192*116*47 (mm)
Build-in size: 177.5*100.5*46.5(mm)



Model: HIS-150

Color/B/W CCD
Dimension: 192*116*47 (mm)
Build-in size: 177.5*100.5*46.5(mm)



Model: HIS-910

Color/B/W CCD
Dimension: 316*136*56(mm)
Build-in size: 280*114*34(mm)